

PRODUCT NAME: SILOX SEAL A SIDE  
PRODUCT CODE: SILOX SEAL A SIDE

HMS CODES: H F R P  
1 0 0 G

===== SECTION I - IDENTIFICATION =====

MANUFACTURER'S NAME: AMTECO, INC.  
DISTRIBUTOR'S NAME : MFG SEALANTS  
ADDRESS : 1841 F MARIETTA BLVD  
ATLANTA, GA 30318  
INFORMATION PHONE : 1-800-297-SEAL(7325)  
EMERGENCY PHONE 1-800-424-9300

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

\*\*\*NO REPORTABLE QUANTITIES OF HAZARDOUS INGREDIENTS ARE PRESENT\*\*\*  
N/A, PAINT, NON-HAZARDOUS - NOT REGULATED

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.00  
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER  
COATING VOC: 0.00 lbs/gal MATERIAL VOC: 0.00 lbs/gal  
SOLUBILITY IN WATER: SOLUBLE  
APPEARANCE AND ODOR: MILKY LIQUID MILD SOLVENT ODOR

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A  
METHOD USED: N/A  
FLAMMABLE LIMITS IN AIR BY VOLUME: LOWER-N/A UPPER-N/A  
EXTINGUISHING MEDIA: USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.  
SPECIAL FIREFIGHTING PROCEDURES: THIS PRODUCT WILL NOT SUPPORT COMBUSTION  
UNUSUAL FIRE AND EXPLOSION HAZARDS: MATERIAL CAN SPLATTER ABOVE 100°C/212°F. DRIED PRODUCT CAN BURN.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE  
CONDITIONS TO AVOID: NONE KNOWN  
INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN  
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE, AND OXIDES OF NITROGEN  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== **SECTION VI - HEALTH HAZARD DATA** =====

**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** INHALATION OF VAPOR OR MIST CAN CAUSE THE FOLLOWING-HEADACHE, NAUSEA, IRRITATION OF NOSE, THROAT AND LUNGS.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** SKIN-PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE MILD IRRITATION AND DRYNESS. EYE-DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION AND DRYNESS.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE MILD IRRITATION AND DRYNESS.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:** MAY CAUSE NAUSEA AND VOMITING.

**HEALTH HAZARDS (ACUTE AND CHRONIC):** NOT KNOWN

**CARCINOGENICITY**

NTP CARCINOGEN: N/A IARC MONOGRAPHS: N/A OSHA REGULATED: N/A

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** NOT KNOWN

**EMERGENCY AND FIRST AID PROCEDURES:** INHALATION-MOVE SUBJECT TO FRESH AIR. RESTORE BREATHING IF NECESSARY. TREAT SYMPTOMATICALLY AND CONSULT PHYSICIAN. EYE & SKIN CONTACT-FLUSH EYES WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES. SEE A PHYSICIAN IMMEDIATELY. WASH SKIN AFTER REMOVING CONTAMINATED CLOTHING WITH MILD SOAP AND WATER FOR 15 MINUTES. SEE PHYSICIAN IF IRRITATION PERSISTS. INGESTION-DRINK 1-2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY. NEVER GIVE LIQUIDS TO AN UNCONSCIOUS PERSON.

===== **SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE** =====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY; USE CARE TO AVOID FALLING. CONTAIN SPILLS IMMEDIATELY WITH INERT MATERIALS (E.G. SAND, EARTH). TRANSFER LIQUIDS AND SOLID DIKING MATERIAL TO SEPARATE SUITABLE CONTAINERS FOR RECOVERY OR DISPOSAL.

**WASTE DISPOSAL METHOD:** DISPOSE OF ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** KEEP FROM FREEZING.

**OTHER PRECAUTIONS:** DO NOT TAKE INTERNALLY

===== **SECTION VIII - CONTROL MEASURES** =====

**RESPIRATORY PROTECTION:** RESPIRATORY PROTECTION PROGRAM MEETING OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. NONE REQUIRED IF AIRBORNE CONCENTRATION IS MAINTAINED BELOW THE EXPOSURE LIMIT LISTED IN "EXPOSURE LIMIT INFORMATION". WEAR A MSHA/NIOSH APPROVED (OR EQUIVALENT) HALF-MASKED, AIR-PURIFYING RESPIRATOR.

**VENTILATION:** USE LOCAL EXHAUST VENTILATION WITH A MINIMUM CAPTURE VELOCITY OF 100 ft/min (0.5 M/sec) AT THE POINT OF VAPOR EVOLUTION.

**PROTECTIVE GLOVES:** NEOPRENE GLOVES RECOMMENDED FOR DIRECT CONTACT.

**EYE PROTECTION:** USE CHEMICAL SPLASH GOGGLES

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** FACILITIES STORING OR UTILIZING THIS MATERIAL SHOULD BE EQUIPPED WITH AN EYE WASH STATION AND SHOWER.

**WORK/HYGIENIC PRACTICES:** WASH HANDS BEFORE AND AFTER EATING, SMOKING AND USING THE BATHROOM.

===== SECTION IX - DISCLAIMER =====

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, NEITHER AMTECO, INC NOR MFG SEALANTS ASSUME ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER.